
venco

www.venco.com.au

MINI PUG



CLAYCORE Pty. Ltd.
47 Newbey St
Milpara, WA 6330
ABN 69 634 757 029

SAFETY INSTRUCTIONS

- ⚠ USE WITH RCD PROTECTED OUTLETS ONLY. IF YOU ARE UNSURE ASK AN ELECTRICIAN OR USE A STAND -ALONE PLUG-IN RCD.
- ⚠ DO NOT OPERATE ELECTRICAL SWITCHES WITH WET HANDS.
- ⚠ ENSURE MINI PUG IS SWITCHED OFF AND UNPLUGGED FROM POWER SOURCE BEFORE CLEANING OR MAINTENANCE AND AFTER OPERATION.
- ⚠ NEVER TAMPER WITH ANY OF THE ELECTRICAL COMPONENTS OF THE MINI PUG AS THERE IS A RISK OF AN ELECTRIC SHOCK.
- ⚠ TO CLEAN THE MINI PUG, USE A WET SPONGE. DO NOT USE A PRESSURISED WATER SOURCE IN THE VICINITY OF THE MACHINE eg. GARDEN HOSE
- ⚠ DO NOT REMOVE THE SAFETY SCREEN.
- ⚠ ENSURE LONG HAIR AND LOOSE CLOTHING ARE SECURED.
- ⚠ ENSURE MACHINE IS OPERATED ON A FLAT AND LEVEL SURFACE.
- ⚠ ENSURE CHILDREN ARE NOT LEFT UNATTENDED NEAR THE MACHINE.
- ⚠ ENSURE TOOLS AND SMALL PARTS ARE OUT OF REACH OF CHILDREN
- ⚠ STOP OPERATION OF THE MINI PUG IF SMOKE IS DETECTED OR THERE ARE UNUSUAL NOISES.
- ⚠ DO NOT INSERT HANDS OR OBJECTS INTO OPENINGS OR MOVING PARTS OF THE MINI PUG.
- ⚠ REPAIR OR MODIFICATION OF THE MINI PUG IS PROHIBITED.



PLEASE NOTE THAT AUDIO NOISE LEVELS ARE 60 Dba.

OPERATING INSTRUCTIONS

- THE MAIN FUNCTION OF THE MINI PUG IS TO MIX AND BLEND SMALL QUANTITIES OF CLAY, SUCH AS TURNINGS SCRAP AND CLAY SCRAP FROM THE POTTER'S WHEEL.
- CLAY NEEDS TO BE THROWING CONSISTENCY AND IT IS CRITICAL THAT THE MINI PUG IS NOT OVERLOADED WITH UNDULY DRY CLAY.
- THE MINI PUG SHOULD NOT BE SWITCHED ON TO CLEAR DRY CLAY IN THE BARREL.
- IN THE EVENT THAT CLAY IS ALLOWED TO DRY OUT IN THE BARREL, TURN OFF THE MINI PUG AND UNPLUG THE POWER SUPPLY. REMOVE THE BARREL AND AUGER AS ONE UNIT. THE BARREL IS HELD ON BY 4 STAINLESS STEEL BOLTS (M6 x 30) AND THE AUGER BY 1 BOLT (M8 x 16mm). YOU WILL REQUIRE 2 x 10mm AND 1 x 13mm SPANNERS.

MAINTENANCE

- BEFORE PERFORMING ANY MAINTENANCE TURN OFF THE MINI PUG AND UNPLUG THE POWER SUPPLY.
- THE BARREL AND AUGER ARE STAINLESS STEEL AND THE BARREL MOUNTING FLANGE (BLACK) IS POLY ACETYL. THESE MATERIALS ARE HIGHLY CORROSION RESISTANT AND HAVE A LONG LIFE EXPECTANCY. WHEN NOT IN USE, SEAL THE NOZZLE END AND THE HOPPER WITH PLASTIC FILM TAPED IN PLACE.
- THE MAIN WORM DRIVE GEARBOX IS SEALED AND LUBRICATED FOR LIFE. THE TAMPER HANDLE SHOULD BE LUBRICATED WITH OIL OR GREASE WHERE IT PIVOTS ON THE BARREL.



THANK YOU FOR PURCHASING A VENCO MINI PUG AND SUPPORTING AUSTRALIAN MANUFACTURING.